

Encap Plus

Professional low-moisture encapsulator



Encap Plus is an advanced low moisture encapsulating cleaner providing tough grease cutting action with a genuine, brittle dry-down and effective anti-resoiling technology. This outstanding cleaner also includes fluorochemical and

good foaming action which assists operators to track their progress.

BENEFITS

- **Encapsulating** – an advance blend of high performance embrittling and encapsulation agents encapsulate the emulsified soil, embrittling it for easy vacuum removal.

Wool Friendly Action – Exceeds the requirements for the safe cleaning of wool carpeting. It has been carefully engineered to maximise cleaning on both woollen and synthetic fibres (including 5th generation nylon), giving you total peace-of-mind. This has been verified and certified by the Woolsafe Organisation.



- **User Friendly** – low odour formula.
- **More Soil Removal** – Precisely balanced emulsification performance and embrittling ability, allowing a larger amount of soil to be removed by subsequent dry vacuuming.
- **Commercial Compatible** – ideal for commercial carpet – no rinsing required, faster cleaning rates, reduced recurring stains and no rapid resoiling.
- **Economical in Use** – Concentrate formula providing economical 1:32 dilution rates and outstanding cleaning action. Giving you an unbeatable encapsulating cleaner which doesn't break your pocket.

PRODUCT SPECIFICATIONS

Product code: AP460

pH: N.A.

Dilution: 1:32

Fragrance: Powder Fresh

Safety: Non-hazardous

Colour: Clear, blue liquid

Substrate Suitability: All fibre safe

Packaging: 5Lt & 20Lt



Encap Plus

Professional low-moisture encapsulator

DIRECTIONS for USE

Always pretest in an inconspicuous location for fibre and dye sensitivity.

1. Vacuum carpet to remove loose soil.
2. Mix 250ml Encap Plus with 8 Litre clean water.
3. Apply solution to the carpet through the shampoo tank or use a course spray. (1Lt of solution will cover 5 to 20m² depending on the carpet pile density.
4. Scrub/agitate the treated area using a low speed scrubber with a carpet brush or white pad.
5. Allow carpet to dry (30 to 60 min) before opening to traffic.
6. Encapsulated soils will be removed by subsequent dry vacuuming. (Leave for at least 24 hrs before vacuuming.)

